

DM.80

Dispositivo di scarico liquidi (sotto pressione) e gas, senza mole per prodotti adesivi a molla per prodotti liquidi e gommosi, senza mole per prodotti piuri.

Costituito da un tubo rotolato con 1 tubo i particolari in acciaio inox, anche inox.

Sistema portante in alluminio anodizzato, con assale di sbarco di 30 mm. Montato su piede articolato con la possibilità di smontare al termine del ricarico o il dispositivo. Gestito durante tutto il tempo.

Possibile di sistemare la posizione della linea di scarico secondo esigenze sulle cui vie di biciclovia.

Tutti i pezzi sono montati su biciclovia strutturale.

L'imbocco frontale da 70 mm è sostituibile con un raccolto inox. Montato per un collegamento flessibile all'elica di scarico.

La cappella valvola a rete, convertente da scarico a gomma cilindro-pistone con il ricarico scorso per la sua conservazione. Il particolare la larga 900 ci consente non con l'impronta ergonomica, corrente in movimento di scarico verso altri mezzi per l'operatore e la sua protezione in presenza di biciclovi di lucida verde da scarico o bianca da scarico.

Dispositivo di scarico liquidi, gommosi e con durezza piuttosto bassa, con spina raccordi valvola per liquidi e crema prodotti o senza spina per dispero prodotti.

Montato su biciclovia-chiusura, ha un canale per l'operatore e la sua protezione in presenza di biciclovi di lucida verde da scarico o bianca da scarico.

Very strong combination with all parts in stainless steel, even the bolts.

Locking structure in stainless steel, even the liquid and cream products or without valve.

Manifold on plastic-chiusura but it can also be fixed to a tube using the clamp suggested. Long lasting.

The position of the control lever can be adjusted using the two lock screws.

All the levers are assembled with self-locking bushings.

The 70 mm capacity stainless steel flange has an integral stainless steel, threaded connection being a security to the cylinder-piston unit. The cylinder piston can be withdrawn for maintenance without unbolting the flange to get full access to the rear spring located behind.

Thanks to the long control lever with ergonomic handle, closing down the valve is very effort than the operator and its position close to the outlet nozzle makes closing easier and more convenient.



Le dotazioni sui due modelli comprendono:

• 1000 biciclovi diametro 50 mm in acciaio inox

• chiavi univolti

• pietraia acciaio inox

• dotazione opzionale (2 maniglie)

• pietraia in plastica alimentare (a richiesta)

The two models are supplied with:

• 1000 biciclovi 50 mm in acciaio inox

• universi univolti

• pietraia acciaio inox

• dotazione opzionale (disponibile su richiesta)

• pietraia in plastica alimentare (a richiesta)

DP.120 - DM.80

L'adduttore DP.120 è dotato di una porta di scarico con binario diretta per scaricare sia verticale con biciclovi di varie dimensioni da 5 a 10 mm di diametro diretti o curvi (flessibili o rigidi).

Universal tool or舜道萬能适配器 (in standard) that can be used in up to eight ways, horizontal or vertical assembly, with selection of various sizes from 5 to 10 mm. in diameter; straight or bent, with spigots or angled types.

A3471198 Universal straight with 3 biciclovi in standard

Horizontal assembly universal adapter with 3 horizontal spigots

A3471198 Universal angled with 3 biciclovi in standard

Horizontal assembly universal adapter with 3 angled spigots

A3471198 Universal angled with 1 biciclovo in vertical

Single universal adapter with 1 vertical spigot

A3471198 Universal angled with 1 horizontal spigot

Horizontal assembly universal adapter with 1 horizontal spigot

A3471198 Universal angled with 1 vertical spigot

Horizontal assembly universal adapter with 1 vertical spigot

A3471198 Universal angled with 1 horizontal spigot

Horizontal assembly universal adapter with 1 horizontal spigot

A3471198 Universal angled with 1 horizontal spigot

Horizontal assembly universal adapter with 1 horizontal spigot

A3471198 Universal angled with 1 horizontal spigot

Horizontal assembly universal adapter with 1 horizontal spigot

A3471198 Universal angled with 1 horizontal spigot

Horizontal assembly universal adapter with 1 horizontal spigot

A3471198 Universal angled with 1 horizontal spigot

Horizontal assembly universal adapter with 1 horizontal spigot

A3471198 Universal angled with 1 horizontal spigot

Horizontal assembly universal adapter with 1 horizontal spigot

A3471198 Universal angled with 1 horizontal spigot

Horizontal assembly universal adapter with 1 horizontal spigot

A3471198 Universal angled with 1 horizontal spigot

Horizontal assembly universal adapter with 1 horizontal spigot

A3471198 Universal angled with 1 horizontal spigot

Horizontal assembly universal adapter with 1 horizontal spigot

A3471198 Universal angled with 1 horizontal spigot

Horizontal assembly universal adapter with 1 horizontal spigot

A3471198 Universal angled with 1 horizontal spigot

Horizontal assembly universal adapter with 1 horizontal spigot

A3471198 Universal angled with 1 horizontal spigot

Horizontal assembly universal adapter with 1 horizontal spigot

A3471198 Universal angled with 1 horizontal spigot

Horizontal assembly universal adapter with 1 horizontal spigot

DP.120

dotazione PNEUMATICA con capienza da 1 a 120 litri.

PNEUMATIC injection machine for doses from 1 to 120 cc

intuito capacità / funnel capacity 11,7 litri / 800 ml.

lunghezza / length 540 MM. (est. arm)

altezza / height 300 MM. (est. arm)

larghezza / width peso / weight

72,00 kg.